



**Cables Cadenas
y Bandas de México**
S.A. de C.V.

CHAIN - HIGH TEST CHAIN GRADE 43

High Test Chain (Grade 43)

Bright or hot galvanized. According to ASTM A413 and NACM Specification.

Proof tested to 2x the Working Load Limit.



Nominal Size Mm	Nominal Size Inches	Working Load Limit in Pounds	Feet per Drum	Max. Length per 100 links	Minimum Weight per Foot
7	1/4	2,600	800	124.0"	0.63
8	5/16	3,900	550	129.1"	0.93
10	3/8	5,400	400	137.8"	1.41
13	1/2	9,200	200	179.1"	2.4
16	5/8	13,000	150	220.5"	3.58
20	3/4	20,200	100	275.6"	5.48

CAUTION: NEVER EXCEED THE WORKING LOAD LIMIT OF CHAIN. NEVER USE PROOF COIL CHAIN FOR OVERHEAD LIFTING OR WHERE ITS FAILURE WILL CAUSE DAMAGE TO PROPERTY OR LIFE.



**Cables Cadenas
y Bandas de México**
S.A. de C.V.

Chain Grade 30

Proof Coil

Bright, zinc plated or hot galvanized. According to ASTM A413 and NACM Specification.
Proof tested to 2x the Working Load Limit.



Nominal Size mm	Nominal Size (Plg.)	Working Load Limit in Pounds	Feet per Drum	Max. Length per 100 links	Minimum Weight per Foot
4	1/8	400	1,000	90.5"	0.17
5.5	3/16	800	800	96.4"	0.33
7	1/4	1,300	400	124.0"	0.63
8	5/16	1,900	275	129.1"	0.93
10	3/8	2,650	400	137.8"	1.41
13	1/2	4,500	200	179.1"	2.40
16	5/8	6,900	150	220.5"	3.58
20	3/4	10,600	100	275.6"	5.48
22	7/8	12,800	75	258.7"	7.31
26	1	17,900	60	287.8"	9.41

**CAUTION: NEVER EXCEED THE WORKING LOAD LIMIT OF CHAIN.
NEVER USE PROOF COIL CHAIN FOR OVERHEAD LIFTING OR WHERE ITS
FAILURE WILL CAUSE DAMAGE TO PROPERTY OR LIFE.**



**Cables Cadenas
y Bandas de México**
S.A. de C.V.

Chain Grade 30

Long Link Bumper Mooring Chain

Hot galvanized.

Bright, zinc plated or hot galvanized. According to ASTM A413 and NACM Specification.

Proof tested to 2x the Working Load Limit.



Nominal Size Mm	Nominal Size (Plg.)	Working Load Limit in Pounds	Feet per Drum	Inside Legtn (Plg.)	Inside Width (Plg.)	Minimum Weight per Foot
9.5	3/8	2,650	400	21/2	11/8	1.14
13	1/2	4,500	200	31/2	11/8	2.42
16	5/8	6,900	150	41/2	11/8	3.41
20	3/4	10,600	100	5	11/2	4.91
25.4	1	17,900	60	51/4	11/2	8.82

**CAUTION: NEVER EXCEED THE WORKING LOAD LIMIT OF CHAIN.
NEVER USE PROOF COIL CHAIN FOR OVERHEAD LIFTING OR WHERE ITS
FAILURE WILL CAUSE DAMAGE TO PROPERTY OR LIFE.**