

HMPE Slings HammerHead Slings

| Part. No. | Vertical | Choker | Vertical Basket | Min Length | Rope Dia. | Appx. Slings Dia. | Approx. wgt per linar foot of sling |
|-----------|----------|---------|--------------------|---------------|--------------|----------------------|-------------------------------------|
| HH-9-EPC | 5,700 | 4,600 | 11,500 | 2′ | 3/8" | 1/2" | 0.09 |
| HH-11-EPC | 6,900 | 5,500 | 13,800 | 2′ | 7/16" | 9/16" | 0.11 |
| HH-12-EPC | 10,300 | 8,200 | 20,600 | 2′ | 1/2" | 11/16" | 0.16 |
| HH-16-EPC | 16,900 | 13,500 | 33,900 | 2′ | 5/8" | 7/8" | 0.27 |
| HH-18-EPC | 22,600 | 18,000 | 45,200 | 2′ | 3/4" | 1" | 0.33 |
| HH-22-EPC | 30,500 | 24,400 | 61,000 | 2.5′ | 7/8" | 1-3/16" | 0.49 |
| HH-24-EPC | 36,300 | 29,000 | 72,600 | 2.5′ | 1" | 1-3/8" | 0.59 |
| HH-28-EPC | 48,500 | 38,800 | 97,000 | 3′ | 1-1/8" | 1-1/2" | 0.80 |
| HH-30-EPC | 54,400 | 43,500 | 108,800 | 3′ | 1-1/4" | 1-5/8" | 0.91 |
| HH-36-EPC | 72,000 | 58,000 | 145,000 | 3.5′ | 1-1/2" | 2" | 1.29 |
| HH-40-EPC | 96,000 | 76,000 | 192,000 | 3.5′ | 1-5/8" | 2-3/16" | 1.65 |
| HH-44-EPC | 103,000 | 82,000 | 207,000 | 4′ | 1-3/4" | 2-3/8" | 1.95 |
| HH-48-EPC | 117,000 | 93,000 | 234,000 | 4′ | 2" | 2-5/8" | 2.28 |
| HH-52-EPC | 141,000 | 112,000 | 282,000 | 4.5′ | 2-1/8" | 2-7/8" | 2.73 |
| HH-56-EPC | 158,000 | 126,000 | 317,000 | 4.5´ | 2-1/4" | 3" | 3.05 |
| HH-60-EPC | 174,000 | 139,000 | 349,000 | 5′ | 2-1/2" | 3-3/8" | 3.70 |
| HH-64-EPC | 196,000 | 157,000 | 393,000 | 5′ | 2-5/8" | 3-1/2" | 4.18 |
| HH-68-EPC | 217,000 | 174,000 | 435,000 | 6′ | 2-3/4" | 3-5/8" | 4.68 |
| HH-72-EPC | 257,000 | 205,000 | 514,000 | 6.5′ | 3″ | 4" | 5.35 |
| HH-76-EPC | 280,000 | 224,000 | 561,000 | 6.5′ | 3-1/8" | 4-1/8" | 5.88 |
| HH-80-EPC | 310,000 | 248,000 | 620,000 | 6.5′ | 3-1/4" | 4-3/8" | 6.53 |
| HH-84-EPC | | 292,000 | 7 31,000 | 7.5′ | 3-1/2" | 4-5/8" | 7.45 |
| HH-88-EPC | 412,000 | 330,000 | 825,000 | 7.5′ | 3-5/8" | 4-7/8" | 8.10 |
| HH-96-EPC | 501,000 | 401,000 | 1,003,000 | 8.5′ | 4" | 5-3/8" | 9.85 |



- High Strength
- Light Weight
- Durable
- Repairable
- Low Stretch
- 100% Proof Tested



*It is recommended to use the Hammerhead. Sling utilizing a 3:1 D/d, however additional testing has shown no reduction in work load at a 2:1 D/d.

** Vertical basket capacity is based on 6:1 D/d.

