


Shackle 120 Tons.

Alloy Steel Bolt Type Anchor Shackles

** For sizes 1.1/2" - 3": Minimum Width Between Eyes as defined by Federal Specification RR-C-271, current revision.

Meets the performance requirements of Federal Specification RR-C-271, current revision, Type IV A, Class 3, Grade B for sizes 1.1/2" through 3". All sizes forged all-alloy steel, heat treated, permanently marked with size and Working Load Limit.



* U.S. Registered Trademark No. 2,011,393

I	Size in	Working Load	Bolt Ø in	Length Inside in Inches (C)	Width between eyes in Inches (D)		Dimensions in Inches		
Ľ	Inches (A)	Limit in Tons	Inches (B)		Nominal	Tolerance	E	F	Each in Pounds
	1 1/2	30	1 5/8	5 3/4	2 3/8	± 1/8	3 3/4	3 3/8	19.7
l	1 3/4	40	2	7	2 7/8	± 3/16	4 1/2	4 1/2	32.6
L	2	55	2 1/4	7 3/4	3 1/4	± 3/16	5 1/4	5 1/4	48.3
ı	2 1/2	85	2 3/4	10 1/2	4 1/8	± 1/4	6 1/4	6 3/4	94
L	3	120	3 1/4	13	5	± 1/4	6 3/4	7 3/8	145
	3 1/2	150	3 3/4	15	5 1/2	± 1/4	8 1/2	9	250
	4	175	4 1/4	15	5 1/2	± 1/4	9 1/2	10 1/2	358

CAUTION: NEVER EXCEED THE WORKING LOAD LIMIT.

