



**Cables Cadenas
y Bandas de México**
S.A. de C.V.

Ficha Tecnica Galvanized Shackles

Screw Pin Anchor

Load Rated shackles have a brown-painted pin and rating is embossed in the shackle body.

Load-rated shackles conform to federal spec.RR-C-271D, Type IV A, Class 2, Grade A, Amendment 1.

Hot galvanized, forged carbon steel, heat treated, with alloy pins, permanently marked with size.



Nominal Size mm	Nominal Size Inches	Working Load Limit in Tons	Pin Diameter in Inches	Approximate Weight Each in Pounds
4.76	3/16	0.33	1/4	0.05
6.35	1/4	0.5	5/16	0.13
7.93	5/16	0.75	3/8	0.21
9.52	3/8	1	7/16	0.33
11.11	7/16	1.5	1/2	0.47
12.7	1/2	2	5/8	0.78
15.87	5/8	3.25	3/4	1.44
19.05	3/4	4.75	7/8	2.3
22.22	7/8	6.5	1	3.5
25.4	1	8.5	1 1/8	5
28.57	1 1/8	9.5	1 1/4	7
31.75	1 1/4	12	1 3/8	9.5
34.92	1 3/8	13.5	1 1/2	13
38.1	1 1/2	17	1 5/8	16.5
44.45	1 3/4	25	2	29
50.8	2	35	2 1/4	43
63.5	2 1/2	55	2 3/4	86

CAUTION: NEVER EXCEED THE WORKING LOAD LIMIT.



**Cables Cadenas
y Bandas de México**
S.A. de C.V.

Ficha Tecnica Galvanized Shackles

Bolt Type Anchor

Load Rated shackles have a brown-painted pin and rating is embossed in the shackle body.

Load-rated shackles conform to federal spec. RR-C-271D, Type IV A, Class 3, Grade A.

Hot galvanized, forged carbon steel, heat treated, with alloy bolts, permanently marked with size.



Nominal Size mm	Nominal Size Inches	Working Load Limit in Tons	Pin Diameter in Inches	Approximate Weight Each in Pounds
6.35	1/4	0.5	5/16	0.13
7.93	5/16	0.75	3/8	0.21
9.52	3/8	1	7/16	0.33
11.11	7/16	1.5	1/2	0.47
12.7	1/2	2	5/8	0.78
15.87	5/8	3.25	3/4	1.44
19.05	3/4	4.75	7/8	2.3
22.22	7/8	6.5	1	3.5
25.4	1	8.5	1 1/8	5
28.57	1 1/8	9.5	1 1/4	7
31.75	1 1/4	12	1 3/8	9.5
34.92	1 3/8	13.5	1 1/2	13
38.1	1 1/2	17	1 5/8	16.5
44.45	1 3/4	25	2	29
50.8	2	35	2 1/4	43
63.5	2 1/2	55	2 3/4	86
76.2	3	85	3 1/4	145

CAUTION: NEVER EXCEED THE WORKING LOAD LIMIT.



**Cables Cadenas
y Bandas de México**
S.A. de C.V.

Ficha Tecnica Galvanized Shackles

Screw Pin Chain

Straight bow design. Pin screws into the opposite side for Easy installation and removal. Meets the performance requirements of Federal Specification RR-C-271D, Type IV B, Class 2, Grade A. Amendment 1. Hot galvanized, forged carbon steel, heat treated, with alloy pins, permanently marked with size Working Load Limit.



Nominal Size mm	Nominal Size Inches	Working Load Limit in Tons	Pin Diameter in Inches	Approximate Weight Each in Pounds
6.35	1/4	0.5	5/16	0.13
7.93	5/16	0.75	3/8	0.21
9.52	3/8	1	7/16	0.33
11.11	7/16	1.5	1/2	0.47
12.7	1/2	2	5/8	0.78
15.87	5/8	3.25	3/4	1.44
19.05	3/4	4.75	7/8	2.3
22.22	7/8	6.5	1	3.5
25.4	1	8.5	1 1/8	5
28.57	1 1/8	9.5	1 1/4	7
31.75	1 1/4	12	1 3/8	9.5
34.92	1 3/8	13.5	1 1/2	13
38.1	1 1/4	17	1 5/8	16.5
44.45	1 3/4	25	2	29
50.8	2	35	2 1/4	43

CAUTION: NEVER EXCEED THE WORKING LOAD LIMIT.



**Cables Cadenas
y Bandas de México**
S.A. de C.V.

Ficha Tecnica Galvanized Shackles

Bolt Type Chain

Meets the performance requirements of Federal Specification RR-C-271D, Type IV B, Class 3, Grade A, Amendment 1. Hot galvanized, forged carbon steel, heat treated, with alloy pins, permanently marked with size and Working Load Limit.



Nominal Size mm	Nominal Size Inches	Working Load Limit in Tons	Pin Diameter in Inches	Approximate Weight Each in Pounds
6.35	1/4	0.5	5/16	0.13
7.93	5/16	0.75	3/8	0.21
9.52	3/8	1	7/16	0.33
11.11	7/16	1.5	1/2	0.47
12.7	1/2	2	5/8	0.78
15.87	5/8	3.25	3/4	1.44
19.05	3/4	4.75	7/8	2.3
22.22	7/8	6.5	1	3.5
25.4	1	8.5	1 1/8	5
28.57	1 1/8	9.5	1 1/4	7
31.75	1 1/4	12	1 3/8	9.5
34.92	1 3/8	13.5	1 1/2	13
38.1	1 1/2	17	1 5/8	16.5
44.45	1 3/4	25	2	29
50.8	2	35	2 1/4	43

CAUTION: NEVER EXCEED THE WORKING LOAD LIMIT.