



**Cables Cadenas
y Bandas de México**
S.A. de C.V.

Ficha Tecnica Steel Shackles

Screw Pin "D"

Stainless Steel Finish



Nominal Size mm	Nominal Size Inches	Working Load Limit in Tons	Pin Diameter in Inches	Approximate Weight Each in Pounds
6.35	1/4	0.5	5/16	0.13
7.93	5/16	0.75	3/8	0.21
9.52	3/8	1	7/16	0.33
11.11	7/16	1.5	1/2	0.47
12.7	1/2	2	5/8	0.78
15.87	5/8	3.25	3/4	1.44
19.05	3/4	4.75	7/8	2.3
22.22	7/8	6.5	1	3.5
25.4	1	8.5	1 1/8	5
28.57	1 1/8	9.5	1 1/4	7
31.75	1 1/4	12	1 3/8	9.5
34.92	1 3/8	13.5	1 1/2	13
38.1	1 1/4	17	1 5/8	16.5
44.45	1 3/4	25	2	29
50.8	2	35	2 1/4	43

CAUTION: NEVER EXCEED THE WORKING LOAD LIMIT.



**Cables Cadenas
y Bandas de México**
S.A. de C.V.

Ficha Técnica Steel Shackles

Type 316



Nominal Size Inches	Working Load Limit in lbs	Aproximate Weigth Each in Pounds
1/4	1,000	0.11
5/16	1,500	0.22
3/8	2,000	0.45
7/16	3,000	0.75
1/2	4,000	0.90
5/8	6,000	1.68
3/4	8,000	2.75
7/8	10,000	3.40
1	12,000	4.80
1 1/4	14,000	11.71
1 1/2	18,500	20.80

CAUTION: NEVER EXCEED THE WORKING LOAD LIMIT.



**Cables Cadenas
y Bandas de México**
S.A. de C.V.

Stainless Screw Pin Anchor Shackles

TYPE 304 or 316

Forged

Dimensions are the same as
Galvanized Screw Pin
Anchor Shackles



Nominal Size mm	Nominal Size Inches	Working Load Limit inTons	Pin Diameter in Inches	Aproximate Weigth Each in Pounds
4.76	3/16	300	1/4	.04
6.35	1/4	450	5/16	.10
7.93	5/16	650	3/8	.18
9.52	3/8	1,000	7/16	.29
12.70	1/2	1,990	5/8	.74
15.87	5/8	3,050	3/4	1.4
19.05	3/4	4,475	7/8	2.3
22.22	7/8	6,000	1	3.5
25.4	1	7,950	1 1/8	5.1

CAUTION: NEVER EXCEED THE WORKING LOAD LIMIT.