



**Cables Cadenas
y Bandas de México**
S.A. de C.V.

TURNBUCKLE

Drop-forged Carbon Steel With Hot Galvanized Finish.

Meets federal spec. FF-791b, Type 1 Form 1.

Warning! Do not exceed working load limit (WLL).



Size (Plg.)	Item No. Hook & Eye	Item No. Hook & Hook	Item No. Eye & Eye	Item No. Jaw & Jaw	Item No. Jaw & Eye	Working Load Limit (Pound)	H &E H & H E & E (Pound)	Q &Q Q&E (Pound)
1/4 X 4	-	125H25	125E15	125J15	125JE15	400	0.4	0.4
5/16 X 4 1/2	125HE20	125H10	125E10	125J30	-	700	0.5	0.5
3/8 X 6	125HE40	125H30	125E25	125J25	125JE25	1000	0.75	0.82
1/2 X 6	125HE30	125H35	125E35	125J35	125JE35	1500	1.5	1.62
1/2 X 9	125HE36	125H36	125E35A	125J35A	125JE55A	1500	1.75	1.82
1/2 X 12	125HE38	125H37	125E35B	125J35B	125JE35B	1500	2.18	2.19
5/8 X 6	125HE46	125H45	125E45	125J45	125JE45	2250	2.63	2.69
5/8 X 9	125HE47	125H46	125E45A	125J45A	125JE45A	2250	3	3.01
5/8 X 12	125HE45P	125H47	125E45B	125J45C	125JE45B	2250	3.25	3.5
5/8 X 18	-	-	125E48	125J50	-	3500	3.9	3.9
3/4 X 6	125HE48	125H50	125E50	125J50A	125JE50	3000	3.75	4.25
3/4 X 9	125HE50	125H51	125E50A	125J50B	125JE50A	3000	4.5	5
3/4 X 12	125HE45P	125H52	125E50BC	125J50C	125JE50B	3000	5.75	5.75

CAUTION: NEVER EXCEED THE WORKING LOAD LIMIT OF CHAIN. NEVER USE PROOF COIL CHAIN FOR OVERHEAD LIFTING OR WHERE ITS FAILURE WILL CAUSE DAMAGE TO PROPERTY OR LIFE.



**Cables Cadenas
y Bandas de México**
S.A. de C.V.

TURNBUCKLE

Drop-forged Carbon Steel With Hot Galvanized Finish.

Meets federal spec. FF-791b, Type 1 Form 1.

Warning! Do not exceed working load limit (WLL).

Size (Plg.)	Item No. Hook & Eye	Item No. Hook & Hook	Item No. Eye & Eye	Item No. Jaw & Jaw	Item No. Jaw & Eye	Working Load Limit (Pound)	H & E H & H E & E	(Pound) Q & Q Q & E
3/4 X 18	-	125H53	125E51C	125J55	125JE51	3000	7	7.25
7/8 X 12	-	-	125E54	125J55A	125JE54	7200	8.38	8.88
7/8 X 18	125HE60	-	125E55	125J60	125JE55	5000	10.25	10.6
1 X 6	-	125H63	125E60	125J60A	125JE60	1000	8.76	11.1
1 X 12	-	-	125E60A	125J60B	125JE60A	5000	11.25	12
1 X 18	-	-	125E60B	125J60C		5000	14	14.75
1 X 24	-	-	125E60BC	125J75	125JE60C	10000	17	17.75
1 1/4 X 12	-	-	125E75	125J75A	125JE75	15200	19	21.2
1 1/4 X 18	-	-	125E75A	125J75B	125JE75A	15200	24.1	26
1 1/4 X 24	-	-	125E75B	125J95	125JE75B	15200	25	28.7
1 1/2 X 12	-	-	125E95	125J95A	125JE95	21400	27	31.1
1 1/2 X 18	-	-	125E98	125J99	125JE98	21400	31.2	36.4
1 1/2 X 24	-	-	-	-	125JE99	21400	-	44.2
1 3/4 X 24	-	-	-	-	125JE98P	28000	-	61
2 X 24	-	-	-	-	125J100	37000	-	115
2 1/2 X 24	-	-	-	-	125J150	60000	-	180

CAUTION: NEVER EXCEED THE WORKING LOAD LIMIT OF CHAIN. NEVER USE PROOF COIL CHAIN FOR OVERHEAD LIFTING OR WHERE ITS FAILURE WILL CAUSE DAMAGE TO PROPERTY OR LIFE.